

**Product: Liquid Paraffin (Heavy)**

<b>Test</b>	<b>Method</b>	<b>Typical Specifications</b>
Appearance	ST 0061	Bright & Clear, Free from Fluorescence
Density at 15° C	ASTM D - 1298	0.855 - 0.865
Colour Saybolt	ASTM D - 156	Min + 30
Pour Point	ASTM D - 97	Max -9
Flash Point (Coc)	ASTM D - 92	Min 220° C
Kinematic Viscosity @ 40° C	ASTM D - 445	65 - 75
Odour	Ol factory	Odourless
Solid Paraffins	USP	Passes
Acidity & Alkalinity	USP	Passes
Infra Red Scan		Confirms To Standards
Readily Carbonisable Substances	ASTM D - 4530	Passes
U.V. Absorption (240 - 280 Nm)		Passes
Aromatic Polycyclic Hydrocarbons (260 - 350 Nm)	U.S.P.	Passes

---

The above data is indicative only. Minor variations, which do not affect product performance or quality, may be expected in manufacturing.

Tailor made products also available on request.

---

**Note:**

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no