

Product: Light Liquid Paraffin / White Mineral Oil

Test	Method	Typical Specifications
Appearance	ST 0061	Bright & Clear, Free from Fluorescence
Density at 15° C	ASTM D - 1298	0.820 - 0.840
Colour Saybolt	ASTM D - 156	+ 30
Pour Point	ASTM D - 97	Max -9
Flash Point (Coc)	ASTM D - 92	Min 180° C
Kinematic Viscosity @ 40° C	ASTM D - 445	13.5 - 16.5
Odour	Ol factory	Odourless
Solid Paraffins	USP	Passes
Acidity & Alkalinity	USP	Passes
Readily Carbonisable Substances	ASTM D - 4530	Passes
U.V. Absorption (240 - 280 Nm)		Max 0.10 (Passes)
Aromatic Polycyclic Hydrocarbons (260 - 350 Nm)	U.S.P.	Max 0.12 (Passes)

The above data is indicative only. Minor variations, which do not affect product performance or quality, may be expected in manufacturing.

Tailor made products also available on request.

Note:

The information contained herein is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. There is no implied warranty of merchantability or fitness for purpose of the product or products described herein. In submitting this information, no